

Tyre size	Metric Equivalent	Service index	Rim choice	Rim used	Measured at		Diameter		Section		Tread		Revolutions		Average	Approximate
					PSI	Bar	Ins	mm	Ins	mm	Ins	mm	Miles	Km	Weight Kg's	Volume M³
6.0/16.0-10	-	-	6.0 - 7.0	6,0	20	1,4	16,00	407	6,50	166	5,90	151	1258	782	3,20	0,0275
7.0/16.0-10	-	-	7.0 - 8.0	7,0	20	1,4	15,90	404	7,50	190	6,80	172	1268	788	3,55	0,0310
8.5/16.0-10	-	-	8.5 - 9.5	9,0	20	1,4	15,90	403	9,25	235	8,00	203	1268	792	4,27	0,0382
6.0/19.5-13	-	-	5.5 - 6.5	6,0	20	1,4	19,35	491	6,60	168	6,10	154	1042	651	5,45	0,0405
6.5/19.5-13	-	-	5.5 - 7.0	6,0	20	1,4	19,25	488	6,80	173	6,30	160	1048	655	5,47	0,0412
7.0/19.5-13	-	-	5.5 - 8.0	6,0	20	1,4	19,30	490	7,10	180	6,90	175	1045	653	5,74	0,0432
7.5/19.5-13	-	-	6.0 - 8.5	6,0	20	1,4	18,90	480	8,60	218	7,60	193	1067	667	5,55	0,0502
8.0/19.5-13	-	-	7.0 - 9.0	8,0	20	1,4	19,30	490	8,70	221	7,90	200	1045	653	6,14	0,0531
8.5/19.5-13	-	-	8.0 - 10.0	8,0	20	1,4	19,60	497	8,90	226	8,00	203	1029	643	5,56	0,0558
9.0/19.5-13	-	-	9.0 - 11.0	9,0	20	1,4	19,90	505	10,50	267	9,30	236	1013	633	5,96	0,0681
6.2/20.0-13	-	-	5.5 - 6.5	6,0	20	1,4	19,90	505	7,20	183	6,10	154	1013	633	4,76	0,0467
6.5/20.0-13	-	-	5.5 - 7.0	6,0	20	1,4	20,10	510	7,30	185	6,50	165	1003	627	5,39	0,0481
7.0/20.0-13	-	-	6.0 - 8.0	7,0	20	1,4	20,10	510	8,00	203	7,40	187	1003	627	5,36	0,0528
7.2/20.0-13	-	-	6.0 - 8.0	8,0	20	1,4	20,20	513	9,00	229	7,10	180	998	624	5,17	0,0603
7.5/20.0-13	-	-	6.5 - 8.5	8,0	20	1,4	20,25	514	9,00	229	7,70	195	996	622	6,38	0,0605
8.2/20.0-13	-	-	7.0 - 9.0	9,0	20	1,4	19,95	506	9,75	248	8,50	215	1011	632	5,98	0,0635
9.0/20.0-13	-	-	8.0 - 10.0	10,0	20	1,4	20,00	508	10,65	271	9,20	233	1008	630	6,29	0,0699
10.0/20.0-13	-	-	9.0 - 11.0	10,0	20	1,4	19,80	502	11,10	282	10,20	259	1018	636	6,72	0,0711
6.0/21.0-13	-	-	5.5 - 7.0	6,0	20	1,4	20,50	520	7,40	188	6,20	157	984	615	5,09	0,0508
6.5/21.0-13	-	-	5.5 - 7.5	7,0	20	1,4	20,50	520	9,00	229	6,50	165	984	615	5,35	0,0619
7.0/21.0-13	-	-	6.0 - 8.0	8,0	20	1,4	20,60	523	9,00	229	7,20	182	979	612	5,54	0,0626
7.5/21.0-13	-	-	6.5 - 8.5	8,0	20	1,4	20,50	520	8,50	216	7,40	187	984	615	5,62	0,0584
8.0/21.0-13	-	-	7.0 - 9.0	9,0	20	1,4	20,80	528	9,90	252	8,10	206	969	602	6,47	0,0703
8.5/21.0-13	-	-	7.5 - 9.0	9,0	20	1,4	20,80	528	10,20	259	8,60	215	969	606	6,07	0,0722
9.0/21.0-13	-	-	8.0 - 10.0	10,0	20	1,4	21,00	533	10,90	277	9,10	231	960	600	6,83	0,0787
7.0/22.0-13	-	-	6.5 - 8.5	7,5	20	1,4	21,60	548	8,70	221	6,90	175	934	584	6,00	0,0664
8.2/22.0-13	-	-	7.0 - 10.0	9,0	20	1,4	22,00	558	10,10	257	8,60	218	917	573	6,01	0,0800
9.2/22.0-13	-	-	8.5 - 10.5	10,0	20	1,4	22,40	568	11,10	282	9,10	231	900	562	6,88	0,0910
10.0/22.0-13	-	-	9.0 - 12.0	11,0	20	1,4	22,10	561	11,90	302	10,30	261	912	570	7,55	0,0950
10.5/23.0-13	-	-	9.5 - 11.5	11,0	20	1,4	23,50	596	12,30	312	10,30	261	858	536	8,61	0,1108
12.0/23.0-13	-	-	12.0 - 14.0	13,0	20	1,4	23,20	589	14,50	368	12,30	312	869	543	8,80	0,1277
13.0/23.0-13	-	-	13.0 - 15.0	14,0	20	1,4	23,25	590	15,15	385	13,00	330	867	542	8,91	0,1340
14.0/23.0-13	-	-	14.0 - 15.0	14,0	20	1,4	23,25	590	15,55	395	13,60	345	867	542	9,20	0,1375
13.0/24.5-13	-	-	13.0 - 15.0	14,0	20	1,4	24,30	617	15,50	394	12,50	317	830	519	10,01	0,1500
15.0/26.0-13	-	-	15.0 - 18.0	16,0	20	1,4	25,75	654	17,75	451	15,00	381	783	489	12,27	0,1929
16.2/26.0-13	-	-	16.0 - 18.0	17,0	20	1,4	25,80	655	18,75	476	16,30	414	782	489	12,86	0,2042
6.6/19.5-14	-	-	5.5 - 7.5	6,0	30	2,0	20,00	508	7,20	183	6,80	172	1008	630	6,06	0,0472
6.5/21.0-14	-	-	5.5 - 7.0	7,0	20	1,4	21,40	543	7,25	184	7,60	193	942	589	6,37	0,0543
7.0/21.0-14	-	-	5.5 - 8.0	7,0	20	1,4	21,00	533	7,30	184	7,90	200	960	600	5,91	0,0523
7.0/21.5-14	-	-	5.5 - 6.0	5,5	20	1,4	21,90	556	7,75	197	7,00	177	921	576	7,10	0,0609
10.0/21.5-14	-	-	8.5 - 11.0	11,0	20	1,4	22,05	560	11,97	304	9,84	250	915	568	7,01	0,0953

