

Tyre size	Metric Equivalent	Service index	Rim choice	Rim used	Measured at		Diameter		Section		Tread		Revolutions		Average	Approximate
					PSI	Bar	Ins	mm	Ins	mm	Ins	mm	Miles	Km	Weight Kg's	
7.0/21.5-15	-	-	5.5 - 7.5	6,0	30	2,0	22,10	561	7,40	188	7,00	177	912	570	6,50	0,0592
7.5/21.5-15	-	-	6.0 - 8.0	6,0	30	2,0	22,20	563	7,80	198	7,20	182	908	568	7,05	0,0628
8.0/21.5-15	-	-	6.5 - 8.5	7,5	30	2,0	21,80	553	8,80	224	7,80	198	925	578	7,19	0,0685
8.7/21.5-15	-	-	7.5 - 9.0	8,0	30	2,0	22,10	561	9,70	246	8,40	213	912	570	6,98	0,0774
9.5/21.5-15	-	-	8.0 - 10.0	10,0	30	2,0	21,85	554	10,65	271	9,50	241	923	577	7,78	0,0832
10.0/21.5-15	-	-	8.5 - 11.0	10,0	30	2,0	21,85	554	11,00	279	10,00	254	923	577	7,27	0,0856
10.7/21.5-15	-	-	9.0 - 11.0	10,0	30	2,0	21,85	554	11,30	287	10,60	269	923	577	7,41	0,0881
5.0/22.0-15	-	-	5.5 - 6.5	5,5	30	2,0	21,60	549	6,65	169	5,75	146	934	580	4,89	0,0509
8.0/22.5-15	-	-	6.5 - 7.5	7,0	30	2,0	22,45	570	8,95	227	7,75	196	898	561	7,23	0,0738
6.5/23.0-15	-	-	6.0 - 7.5	6,0	30	2,0	23,00	584	7,55	192	6,50	165	877	548	8,78	0,0655
7.0/23.0-15	-	-	6.5 - 8.0	7,0	30	2,0	23,10	586	7,95	202	6,90	175	873	546	8,91	0,0694
7.5/23.0-15	-	-	7.0 - 8.5	8,0	30	2,0	22,80	579	8,50	216	7,40	187	884	552	9,33	0,0724
10.5/23.0-15	-	-	10.0 - 12.0	11,0	30	2,0	23,55	598	11,95	304	10,30	261	856	535	7,94	0,1087
8.5/23.5-15	-	-	7.0 - 9.5	8,5	30	2,0	23,60	599	9,60	244	8,80	223	854	534	9,08	0,0875
9.0/23.5-15	-	-	7.0 - 10.0	8,5	30	2,0	23,60	599	9,90	251	9,30	236	854	534	11,58	0,0901
9.1/23.5-15	-	-	8.0 - 9.5	8,5	30	2,0	23,55	598	9,88	251	8,50	215	856	535	9,36	0,0898
11.0/23.5-15	-	-	10.0 - 12.0	11,0	30	2,0	23,30	591	12,10	307	11,30	287	865	541	9,03	0,1072
12.5/23.5-15	-	-	11.0 - 13.5	12,0	30	2,0	23,30	591	13,30	338	12,70	322	865	541	9,58	0,1181
9.0/25.0-15	-	-	9.0 - 11.0	10,0	30	2,0	24,75	629	10,10	257	8,90	226	815	506	7,95	0,1017
9.5/25.0-15	-	-	9.0 - 11.0	10,0	30	2,0	24,75	628	11,70	297	9,25	234	815	509	9,34	0,1171
11.0/25.0-15	-	-	10.0 - 12.0	12,0	30	2,0	24,70	627	13,60	345	11,30	287	816	510	10,40	0,1356
13.0/25.0-15	-	-	11.5 - 14.5	14,0	30	2,0	24,80	629	15,40	391	13,20	335	813	508	10,59	0,1547
15.0/26.0-15	-	-	15.0 - 17.0	16,0	30	2,0	25,75	654	17,40	442	15,00	381	783	489	12,08	0,1891
16.2/26.0-15	-	-	16.0 - 18.0	16,0	30	2,0	25,80	655	17,90	455	16,30	414	782	489	11,71	0,1952
12.5/27.0-15	-	-	11.5 - 14.5	13,0	30	2,0	27,00	685	15,25	387	12,50	317	747	467	12,19	0,1816
14.0/27.0-15	-	-	13.0 - 16.0	15,0	30	2,0	27,10	688	16,70	424	14,00	355	744	465	12,47	0,2007
16.0/27.0-15	-	-	15.0 - 18.0	16,0	30	2,0	27,50	698	16,80	427	16,10	408	733	458	12,71	0,2080
9.5/21.5-16	-	-	8.0 - 10.0	10,0	30	2,0	21,85	554	10,30	262	9,50	241	923	577	6,85	0,0804
10.7/21.5-16	-	-	9.0 - 11.0	11,0	30	2,0	22,05	560	11,60	295	10,60	269	915	572	7,15	0,0925
7.5/22.5-16	-	-	6.0 - 7.0	6,0	30	2,0	22,65	575	7,65	194	7,30	185	890	556	5,80	0,0641
8.0/22.5-16	-	-	6.5 - 7.5	7,0	30	2,0	22,65	575	8,55	217	7,90	200	890	556	6,46	0,0717
7.0/23.0-16	-	-	5.5 - 7.0	6,0	30	1,4	23,70	601	7,40	188	7,00	177	851	532	8,82	0,0679
7.5/23.0-16	-	-	6.0 - 8.0	7,5	30	1,4	23,80	604	8,45	215	7,50	190	847	529	8,94	0,0784
8.5/23.3-16	-	-	7.5 - 8.0	8,0	30	2,0	23,55	598	9,60	244	8,80	223	856	535	7,72	0,0873
9.0/23.5-16	-	-	8.0 - 9.0	8,0	30	2,0	23,70	601	9,90	251	9,30	236	851	532	6,80	0,0907
8.0/23.5-16	-	-	7.0 - 9.0	8,0	30	2,0	23,70	601	9,00	229	7,80	198	851	532	10,15	0,0827
8.5/23.5-16	-	-	7.5 - 9.5	7,5	30	2,0	23,60	599	8,90	226	8,50	215	854	534	7,74	0,0811
9.5/23.5-16	-	-	8.5 - 10.5	8,5	30	2,0	23,60	599	9,80	249	9,50	241	854	534	8,96	0,0893
10.0/23.5-16	-	-	9.0 - 11.0	10,0	30	2,0	23,60	599	10,95	278	10,00	254	854	534	7,68	0,0997
10.5/23.5-16	-	-	10.0 - 11.5	11,0	30	2,0	23,60	599	11,80	300	10,45	265	854	534	8,00	0,1076
11.0/23.5-16	-	-	10.0 - 12.0	12,0	30	2,0	23,50	596	12,55	319	11,30	287	858	536	8,66	0,1133
12.5/23.5-16	-	-	11.5 - 13.5	13,5	30	2,0	23,40	594	13,75	349	12,70	322	862	539	9,54	0,1231
11.0/25.0-16	-	-	10.0 - 12.0	12,0	30	2,0	24,75	628	13,30	338	11,30	287	815	509	10,24	0,1333
12.5/25.0-16	-	-	11.5 - 13.5	13,0	30	2,0	24,75	628	14,20	361	12,50	317	815	509	11,81	0,1424
13.5/25.0-16	-	-	12.0 - 14.5	14,0	30	2,0	25,00	635	15,20	386	13,40	340	807	504	10,72	0,1556
12.5/27.0-16	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
13.2/27.0-16	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
14.0/27.0-16	-	-	13.0 - 16.0	14,0	30	2,0	27,20	690	15,75	400	14,00	355	741	463	13,07	0,1904
7.5/24.0-17	-	-	7.0 - 8.0	8,0	30	2,1	24,30	618	9,05	230	7,70	195	824	515	9,69	0,0878
8.0/24.0-17	-	-	7.5 - 8.5	8,0	30	2,1	24,50	622	9,45	240	8,07	205	818	512	9,40	0,0929
8.0/25.0-17	-	-	8.0 - 9.0	8,0	20	1,4	25,20	640	9,00	229	8,00	203	800	500	10,70	0,0938
9.0/25.0-17	-	-	8.0 - 10.0	8,5	30	2,0	25,15	638	9,80	249	8,50	215	802	501	10,67	0,1014

