



Gamme Dunlop Historique



Formule Ford

Dimension	Pattern	Permitted Rim Width (inch)	Optimum Rim Width (inch)	Diameter (inch)	Diameter (mm)	Width (inch)	Overall (mm)	Width (inch)	Tread (mm)	Revs Per Mile (at 100mph)
135/545-13	CR82	5.0 - 6.0	5.5	21.7	550	7.5	190	5.3	135	935
165/580-13	CR82	5.0 - 6.0	5.5	23	585	8.3	220	6.5	165	883

L Section (metal locking valve race tubes available)

Size	Pattern	Permitted Rim Width (inch)	Optimum Rim Width (inch)	Diameter (inch)	Diameter (mm)	Width (inch)	Overall (mm)	Width (inch)	Tread (mm)	Revs Per Mile (at 100mph)
500 L10	CR65	3.5 - 5.5	4.5	19.6	498	6.5	165	4.7	120	1029
450 L12	CR65	4.0 - 7.0	5	21.3	540	6.9	175	4.7	118	968
450 L13	CR65	3.5 - 7.0	5	22.1	560	6.6	167	4.5	115	915
550 L13	CR65	4.0 - 7.0	5.5	23.9	608	7.8	199	5	128	844
550 L14	CR65	4.0 - 6.5	5.5	24.8	631	7.8	198	5	128	812
450 L15	CR48 (R6)	3.5 - 6.0	5	24	609	6.1	156	4	102	841
500 L15	CR65	4.0 - 7.0	6	24.8	631	7.4	187	4.7	120	812
550 L15	CR65	4.0 - 7.0	6.5	25.9	659	8	204	5	128	777
600 L15	CR65	5.0 - 7.5	7	26.9	684	8.8	224	5.3	135	749
650 L15	CR65	5.5 - 8.0	7.5	27.8	706	9.4	239	5.6	142	726
700 L15	CR65	6.5 - 9.0	8.5	27.8	706	10.4	265	6.6	167	726
600 L16	CR48 (R6)	5.0 - 7.0	6	27.8	708	7.9	201	4.8	122	724
650 L16	CR48(R6)	5.5 - 7.5	7	28.7	729	8.9	227	5.1	130	703

M Section (all tubeless)

Size	Pattern	Permitted Rim Width (inch)	Optimum Rim Width (inch)	Diameter (inch)	Diameter (mm)	Width (inch)	Overall (mm)	Width (inch)	Tread (mm)	Revs Per Mile (at 100mph)
450M 13	CR65	4.0 - 7.5	5.5	21.7	552	6.7	172	4.9	124	928
525M 13	CR65	5.0 - 8.0	5.5	23.2	590	8.3	210	5.8	148	868
550M 13	CR65	6.0 - 9.0	8	23.7	602	9.9	251	6.9	175	851
550M 14	CR65	5.5 - 8.0	7	25	635	9	228	5.9	150	805
500M 15	CR65	5.5 - 8.0	7.5	25.5	648	8.7	221	6	152	791
550M 15	CR65	6.0 - 8.5	8	26	660	9.5	241	6.5	165	776
600M 15	CR65	7.0 - 9.0	8.5	27	686	10.7	271	7	178	747
650M 15	CR65	7.5 - 10.0	9	28	711	11.6	295	8	203	720

Post Historic (all tubeless)

Size	Pattern	Permitted Rim Width (inch)	Optimum Rim Width (inch)	Diameter (inch)	Diameter (mm)	Width (inch)	Overall (mm)	Width (inch)	Tread (mm)	Revs Per Mile (at 100mph)
175/550-13	CR65	5.5 - 8.0	8	21.9	555	9.1	231	6.8	172	923
475/1000-13	CR65	5.5 - 8.5	8	23.3	593	9.4	239	7.1	181	864
475/1150-13	CR65	7.0 - 10.0	9	22.8	578	10.8	274	8.3	211	886
600/1200-13	CR65	9.0 - 11.0	10	25.2	640	12.3	312	9.4	239	800
600/1350-13	CR65	11.0 - 14.0	12	25	635	13.8	351	10.8	274	807
240/525-13	CR65	10.0 - 12.0	11	20.9	531	10.8	274	9.2	234	967
305/1600-13	CR65	12.5 - 14.0	13.5	23.9	607	15.8	402	12.0	305	845
120/590-15	CR82	4.0 - 5.5	4.5	22.8	579	6.3	161	4.7	120	885
135/620-15	CR82	4.5 - 6.0	4.5	24.3	617	7.5	190	5.4	138	830
475/1000-15	CR65	6.0 - 9.0	8	24.7	627	9.8	249	7.1	181	817
430/1160-15	CR82	7.5 - 11.0	9.5	23.7	622	11.3	287	9.1	231	824
600/1200-15	CR65	9.0 - 11.0	10	26.6	675	12.4	314	9.4	240	759
525/1050-15	CR65	7.5 - 10.0	8.5	25.7	652	10.5	266	8	207	786
530/1360-15	CR82	12.0 - 13.0	12	25.7	653	13.6	345	11.2	284	784
530/1500-15	CR82	14.0 - 15.5	15	25.5	648	16	406	12.6	320	791
530/1600-15	CR82	16.0 - 17.0	17	25.5	648	17.5	445	14.3	364	791

Vintage

Size	Pattern	Permitted Rim Width (inch)	Optimum Rim Width (inch)	Diameter (inch)	Diameter (mm)	Width (inch)	Overall (mm)	Width (inch)	Tread (mm)	Revs Per Mile (at 100mph)
450-15	R5	3.0 - 4.5	4	24	610	5.6	142	3.5	90	840
500-15	R5	3.0 - 5.0	4.5	24.8	630	6.8	173	3.8	96	824
550-15	R5	3.5 - 5.5	5	25.8	655	7.1	180	4.2	107	768
600-15	R5	4.0 - 6.0	5.5	26.6	676	7.7	197	4.6	116	755
650-15	R5	4.5 - 6.5	6	27.4	696	8.4	214	4.9	124	746
550-16*	R5	4.5 - 6.0	5.5	27.1	688	7	178	4.2	106	745
600-16*	R5	4.5 - 6.0	5.5	27.9	708	7.8	198	4.8	121	723
650-16*	R5	4.5 - 6.5	6	28.9	735	8.3	201	4.8	122	698
700-16*	R5	5.5 - 7.5	7	29.1	740	8.8	224	4.9	125	692
550-17*	R5	4.0 - 6.0	4	28.1	713	6.5	165	3.8	97	718
700-17*	R5	5.0 - 7.0	6	30.2	767	8.3	210	4.5	114	668
550, 600-18*	R1	4.0 - 6.5	4.5	30.1	765	6.9	175	4.3	109	670
700-18*	R1	5.0 - 7.0	5	32.1	815	8.8	224	5.4	137	629
500-19*	5 STUD	3.0 - 5.0	4	29.6	753	6.2	157	3.7	93	680
600-19*	5 STUD	4.0 - 6.0	4.5	31	787	6.9	175	4.3	109	651
650-19*	5 STUD	4.0 - 6.0	5	31.6	803	7.8	198	4.6	117	638
700-19*	R1	4.5 - 6.5	5	32.9	837	8.9	224	5.1	130	612
4.50-19*	TRIPLE STUD	2.7 - 4.5	4	28.2	717	5.5	140	3.6	91	715

* Denotes these tyres are Road Legal

