

Tyre size	Metric Equivalent	Service index	Rim choice	Rim used	Measured at		Diameter		Section		Tread		Revolutions		Average	Approximate
					PSI	Bar	Ins	mm	Ins	mm	Ins	mm	Miles	Km	Weight Kg's	Volume M³
200/605R17	-	-	7.0 - 8.0	8,0	29	2,0	24,00	609	8,70	221	7,90	201	837	523	8,90	0,0820
230/605R17	-	-	8.0 - 9.0	9,0	29	2,0	24,00	609	9,85	250	9,20	234	837	523	9,51	0,0927
205/610R17	-	-	7.0 - 8.0	8,0	29	2,0	24,50	622	8,50	215	7,90	201	823	512	8,89	0,0832
215/610R17	-	-	7.0 - 8.0	8,0	29	2,0	24,30	618	9,00	229	9,00	229	829	515	8,90	0,0875
210/620R17	-	-	7.0 - 8.0	7,5	20	1,4	24,20	615	9,00	229	8,25	210	833	518	10,18	0,0866
230/620R17	-	-	8.5 - 9.5	9,0	20	1,4	24,38	619	9,80	249	8,99	228	827	514	9,49	0,0954
250/620R17	-	-	9.5 - 10.5	10,0	20	1,4	24,35	618	11,00	279	10,00	254	828	515	9,99	0,1066
210/635R17	-	-	7.0 - 8.0	8,0	20	1,4	25,00	635	9,10	230	8,10	205	807	501	10,02	0,0927
240/635R17	-	-	8.5 - 9.5	9,0	20	1,4	25,20	640	9,90	251	9,25	235	800	497	10,84	0,1028
255/635R17	-	-	9.5 - 10.5	10,0	20	1,4	25,20	640	10,75	273	9,90	251	800	497	10,04	0,1118
275/635R17	-	-	10.5 - 11.5	11,0	20	1,4	25,20	640	11,60	295	10,50	267	800	497	10,34	0,1208
285/645R17	-	-	9.0 - 11.0	10,0	20	1,4	25,60	649	11,80	300	12,20	311	789	490	8,59	0,1264
300/650R17	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
210/640R18	-	-	8.0 - 9.0	8,0	29	2,0	25,50	648	8,94	227	8,39	213	791	491	9,41	0,0953
225/640R18	-	-	8.0 - 9.0	9,0	29	2,0	25,50	648	10,10	257	8,80	226	790	491	9,74	0,1079
240/640R18	-	-	8.5 - 9.5	9,0	29	2,0	25,40	645	10,80	274	9,40	239	794	493	9,84	0,1140
250/640R18	-	-	9.5 - 10.5	10,0	29	2,0	25,40	645	11,20	284	9,90	251	794	493	10,18	0,1182
335/645R18	-	-	12.5 - 13.5	12,0	29	2,0	25,75	654	13,30	338	13,00	330	783	487	11,73	0,1446
270/650R18	-	-	10.0 - 11.0	11,0	29	2,0	25,80	656	11,90	302	10,70	272	782	486	10,81	0,1300
300/650R18	-	-	11.0 - 12.5	12,0	29	2,0	25,70	653	13,00	329	12,00	304	785	488	11,77	0,1403
255/660R18	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
270/680R18	-	-	10.5 - 11.5	11,0	29	2,0	26,90	683	11,75	298	10,25	260	750	466	11,85	0,1390
285/680R18	-	-	11.0 - 12.0	11,0	29	2,0	27,00	685	11,90	302	11,00	279	747	464	12,47	0,1417
300/680R18	-	-	12.0 - 13.0	12,0	29	2,0	26,85	682	13,00	330	12,00	305	751	467	12,84	0,1535
280/705R18	-	-	11.0 - 12.0	11,0	29	2,0	27,80	706	12,10	307	10,85	276	725	451	12,50	0,1530
320/705R18	-	-	13.0 - 14.0	13,0	29	2,0	27,80	706	13,85	352	12,55	319	725	451	14,07	0,1754
365/720R18	-	-	14.5 - 16.0	14,5	29	2,0	28,39	721	15,94	405	14,37	365	710	441	15,40	0,2105
210/640R19	-	-	8.0 - 9.0	8,0	29	2,0	25,50	648	8,50	216	8,10	207	790	491	9,09	0,0907
225/640R19	-	-	7.5 - 8.5	8,5	29	2,0	25,40	645	10,10	257	8,80	224	794	493	9,45	0,1069
240/640R19	-	-	8.5 - 9.5	9,0	29	2,0	25,40	645	10,80	274	9,40	239	794	493	9,84	0,1140
250/640R19	-	-	8.5 - 10.5	9,0	29	2,0	24,40	645	11,20	284	9,90	251	794	493	10,17	0,1182
270/680R19	-	-	10.5 - 11.5	10,5	29	2,0	26,90	683	11,75	298	10,25	260	750	466	11,12	0,1390
285/680R19	-	-	11.0 - 12.0	12,0	29	2,0	27,00	687	12,50	317	11,10	283	746	464	12,41	0,1496
300/680R19	-	-	12.0 - 13.0	12,0	29	2,0	26,85	682	13,00	330	12,00	305	751	467	12,57	0,1535
320/705R19	-	-	13.0 - 14.0	13,0	29	2,0	27,80	706	13,85	352	12,55	319	725	451	13,62	0,1754

